




# INVERLED IP20 TOP TOTAL SE/SA



<b>INVERLED TOP TOTAL</b> - Kit di trasformazione in emergenza per lampade			
<b>Tecnologia</b>	Alimentazione per lampade LED	<b>Funzione</b>	S.E./S.A.
<b>Autonomia</b>	da 60 a 180 minuti	<b>Inhibit - Rest Mode*</b>	S1 (modello autotest tramite controller)
<b>Temperatura di funzionamento</b>	0°C / + 40°C	<b>Polenza</b>	da 10 a 50 W

**CONFORME ALLE NORME VIGENTI:**  
EN 61547 • EN 55015, Classe B • EN 1838 • EN 60598-1 • EN 60598-2-22 • EN 61347-2-7 • EN 62471 • EN 62034(Autotesting Version)

INVERLED IP20 TOP TOTAL SE/SA			
CODICE	ARTICOLO	WATT	AUTONOMIA
60466	INVERLED-TT-10-LFP60	10W	60 min
60467	INVERLED-TT-10-LFP90	10W	90 min
60468	INVERLED-TT-10-LFP120	10W	120 min
60469	INVERLED-TT-10-LFP180	10W	180 min
60470	INVERLED-TT-15-LFP60	15W	60 min
60471	INVERLED-TT-15-LFP90	15W	90 min
60472	INVERLED-TT-15-LFP120	15W	120 min
60473	INVERLED-TT-15-LFP180	15W	180 min
60474	INVERLED-TT-20-LFP60	20W	60 min
60475	INVERLED-TT-20-LFP90	20W	90 min
60476	INVERLED-TT-20-LFP120	20W	120 min
60477	INVERLED-TT-25-LFP60	25W	60 min
60478	INVERLED-TT-25-LFP90	25W	90 min
60479	INVERLED-TT-25-LFP120	25W	120 min
60480	INVERLED-TT-30-LFP60	30W	60 min
60481	INVERLED-TT-30-LFP90	30W	90 min
60482	INVERLED-TT-35-LFP60	35W	60 min
60483	INVERLED-TT-35-LFP90	35W	90 min
60484	INVERLED-TT-40-LFP60	40W	60 min
60485	INVERLED-TT-40-LFP90	40W	90 min
60486	INVERLED-TT-45-LFP60	45W	60 min
60487	INVERLED-TT-50-LFP60	50W	60 min




# INVERLED IP20 MINI SE/SA



<b>INVERLED MINI</b> - Kit di trasformazione in emergenza per lampade			
<b>Tecnologia</b>	Alimentazione per lampade LED	<b>Funzione</b>	S.E./S.A.
<b>Autonomia</b>	da 60 a 180 minuti	<b>Inhibit - Rest Mode*</b>	S1 (mod. standard e autotest tramite controller)
<b>Temperatura di funzionamento</b>	0°C / + 40°C	<b>Polenza</b>	da 4 a 8 W

**CONFORME ALLE NORME VIGENTI:**  
CEI EN55015:2014+A1:2016 • CEI EN61547:2010 • CEI EN61000-3-2:2015 • CEI EN61000-3-3:2014 • EN61000-3-3/EC:2016 • CEI EN62031:2009+A1+A2:2015 • CEI EN61347-1:2016 EN61347-2-13:2015 • A1:2017 • CEI EN60598-2-22:2015 • EC:2016 EN60598-1:2015 • EC:2016 • CEI EN62471:2010 • EN 62034(Autotesting Version)

INVERLED MINI IP20 SE/SA			
CODICE	ARTICOLO	WATT	AUTONOMIA
59312	INVERLED-MINI-4-LFP-10SESA	4W	60 min
71576	INVERLED-MINI-4-LFP-15SESA	4W	90 min
59313	INVERLED-MINI-4-LFP-20SESA	4W	120 min
59314	INVERLED-MINI-4-LFP-30SESA	4W	180 min
59315	INVERLED-MINI-6-LFP-10SESA	6W	60 min
71577	INVERLED-MINI-6-LFP-15SESA	6W	90 min
59316	INVERLED-MINI-6-LFP-20SESA	6W	120 min
59318	INVERLED-MINI-8-LFP-10SESA	8W	60 min
71578	INVERLED-MINI-8-LFP-15SESA	8W	90 min



L'AZIENDA SI RISERVA DI APPORRE VARIAZIONI A SUO INSINDACABILE VOLERE



**KROS**  
ELETTRONICA  
EMERGENCY LIGHTING

FABBRICA ELETTRONICA ITALIANA

MADE IN ITALY

EMAIL: [oen@elettronicakros.it](mailto:oen@elettronicakros.it)  
TEL: 06.9588359 - 347.1931232  
[www.elettronicakros.it](http://www.elettronicakros.it)



KROS GROUP